Appln: No. 10/575,227 SEI-120US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Appln. No:

10/575,227 M. KAWAI et al.

Applicant: Filed:

April 7, 2006

Title:

SCANNER APPARATUS

TC/A.U.:

2625

Examiner:

Ngon Binh Nguyen

Confirmation No.:

6987

Docket No.:

SEI-120

DECLARATION OF MR. TAKESHI CHUJOU UNDER 37 C.F.R. 1.132

Mail Stop Amendment Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

- 1. I am one of the inventors of U.S. Patent No. D514,575 to Sugitani et al. ("D514,575"), which claims the ornamental design of an image reader for a computer.
- 2. I understand that D514,575 issued from U.S. Application No. 29/189,758, which was filed on September 11, 2003 ("U.S. Filing Date"), and which claims priority of JP 2003-022949, which was filed on August 7, 2003 ("Foreign Priority Date").
- 3. I understand that claims of the above-identified utility patent application have been rejected by the Examiner based on D514,575.
- 4. To the extent that the Applicants' invention is described in D514,575, their invention was made prior to the U.S. Filing Date of D514,575, and was thereafter described in D514,575 by me and the other inventors of D514,575.
- 5. I understand that the Applicants prepared a Patent, Utility Model Application Request Paper ("Request Paper") before the U.S. Filing Date of D514,575. Copies of that Request Paper are attached to this Declaration as follows:

- 5.1. A redacted copy of the Request Paper is attached as Exhibit 1.
- 5.2. A redacted copy of an English-language translation of the Request Paper is attached as Exhibit 2.
- 6. The Request Paper illustrates and describes features of an image scanner apparatus, including embodiments of a scanner apparatus shown and described in the Request Paper (Exhibit 1) at, for example, Pages 2/5 and 4/5 and elsewhere.
- 7. As detailed in the following subparagraphs, the Applicants explained their invention to me and the other inventors of D514,575.
 - 7.1. Together with another inventor of D514,575 (Mr. Minoru Sugitani), I attended a meeting ("First Meeting") with the Applicants after they prepared the Request Paper and before the U.S. Filing Date and the Foreign Priority Date of D514,575.
 - 7.2. The First Meeting was held at PFU Limited (the assignee of this application and the assignee of D514,575) in Ishikawa Prefecture of Japan.
 - 7.3. During the First Meeting, Mr. Minoru Sugitani and I learned about the Applicants' invention from the Applicants with reference to their Request Paper.
- 8. As detailed in the following subparagraphs, the Applicants' invention was later explained to the remaining inventors of D514,575.
 - 8.1. During a meeting ("Second Meeting") after the First Meeting, I and Mr. Minoru Sugitani met with the remaining co-inventors of D514,575 (Mr. Shinichi Ohta and Mr. Shuji Hashimoto) and explained the Applicants' invention to them.
 - 8.2. The "Second Meeting" was held at PFU Limited in Ishikawa Prefecture of Japan.
 - 8.3. During the Second Meeting, Mr. Minoru Sugitani and I explained the Applicants' invention to Mr. Shinichi Ohta and Mr. Shuji Hashimoto with reference to all of the figures of the Request Paper.

Appln: No. 10/575,227 **SEI-120US**

9. I and the other inventors of the ornamental design claimed in D514,575 made no inventive contribution to the functional features claimed in this utility patent application.

10. Thus, to the extent that the Applicants' invention is described in D514,575, the relevant subject matter of D514,575 describes the Applicants' work, was derived from the Applicants, and is not an invention "by another."

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name: Takeshi Chujou

Date: December 6, 2010

Exhibit 1 - Request Paper

Exhibit 2 - Translated Request Paper

1108525

EXHIBITS

EXHIBIT 1

Set No See See									
調	複波証書			(*注1:氏	名は黒ボールペンにて署名)	<u> </u>	受付	(担当) 部長	課長・PM
譲	受人 株式会社 ピーコ	エフユー	殿		分は他社と共有の場合のみ 記入。社内においては均等制)	6	国	2000年	<u> </u>
貴社	下記発明考案について国内外で特許、若しくは実用新案登録を受ける権利の全部を 貴社に譲渡したことに相違ありません。 譲渡人 株式会社 ピーエフユー内						画	級天海	門沙地
発明	月考案者氏名・注1(フリガナ)	朱肉印	社員コード	職制コード	所属部課名(内線番号)	依	顏元番号_		
筆	(カワイ マサヨシ)	ap	386201	765702	第二事業部 第一技術部	1	発明日		
頭	川井 政佳		持分(34	L 5-0 %)	(7573 — 2243)	牌	発製番		
2	(カネミツ ノリオ)	(£)	799500	765700	第二事業部	阴発製品名 图 图 图 图 图 图 图 图 图 图 图 图 图 图 图 图 图 图 图			
	金光 憲雄	30	持分(33	54 9 %)	(7171 — 1630)	実			
3	(Pa 15 9: 1)		772437		第二颗都第一枚新部	実施状		_	
	大酒品能	7	持分()		(7171 -4640)	況			
4	() (H)					■1.なし	□2. 共同	引開発
		147	持分(%)	(, —)	契約関係	□3.受託		
5	()	a					^{帰属先:} 出題人:	■1.単独 □2.共 ■1.PFU (₹有 □3.社外 □2.富士通
Ŭ		H4°	持分(%)	(–)	pr.		□3.その他()
名称	イメージスキャナ装置	請求項(案)の数:3	出顧期						
	公知例調査 □知財Gと実施、□独自に実施(検索履歴を添付)、□未調査 脱 ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・								

1. 目 的


本発明は、フラットベッド読取部と、ADF(Auto Document Feeder)を有するイメージスキャナ装置に関し、

- ① 使用する設置環境に合わせ、装置の操作性を変化させることが可能な装置構造。
- ② 装置の占有面積を小さくすることができる装置構造。
- ③ ADFモデル、フラットハット・モデルといった様々なパリエーションモデルを製造側が簡単に設定できること。 上記 ①, ②, ③の達成を目的とする。

2. 構成

【当社の従来技術】

2 つの読取エットを配備し、ADF 使用時の両面読取及びフラットペット゚使用時も兼用構造。 ADF は、装置左側に配備されているため、シューターンの原稿セットは、右利きの人は操作しやすいが、 左利きの人には難しさがあった。また、装置の占有面積は、スタッカの長さも入ってしまう構造であった。




株式会社 PFU


受付番号 03 700040

【本発明】

装置に、ADF 部の読取ユニット2 個 フラットハ・ット・部の読取ユニット 1 個 計 3 個の読取ユニットを実装し、ADEユニットのみでも読取が行える構造とし、ADFユニットが装置原稿が一上の任意の位置に配備でき、かつ ADF の向きを回転可能




<<本発明の図 その1(目的①の部分)>>




受付番号 03700040

<<本発明の図 その2(目的②の部分)>>

ADF を移動して原稿か、の中央に置けば シュータ/スタッカ込みで、最小の占有面積の形態。





原稿か、・を開いたイメージ図


<<本発明の図 その3(目的③の部分)>>

本発明の装置構造によって、(3 つの読取エットと ADF が自由に取り外しもできる形態であること。) ADF 部とフラットベッド部が独立してスキャナとしての機能である、読取が行えるため、

ADFモデル/フラットペット、モデル/ADF+フラットペット、モデル といった 3 種のモデルを製造側が新規に開発を行わずとも、簡単に準備できることができる。

下図の絵は、ADFモデルとフラットベッドモデルを示した図であり、1 例として PCBエニットをどちら側に搭載するかで 2モデルが簡単にできる図を示した。

当然、フラットペッドモデルに ADF を搭載すれば、ADF+FBモデルになる。




特許・実用新案 出願依頼書


受付番号 03 P00040

<<本発明の図 その4(目的達成技術>> 下図の機構で原稿カバーとADFの接合を行う。

ADFユニット底面から突起(爪形状)を形成し、原稿か、に配備した穴に差し込む機構。 (向きも変えられる)




回転支点/爪を配備したスライダを 原稿カバーにレール機構で差込むことで左右に移動可能。 また、スライダには回転支点があり、ADFの向きを変えることが可能。 ADF 向きの保持は、スライダに実装されたロック機構(爪)で行う。



原稿カバーとADFの接合機構図株式会社 PFU

<<本発明の図 その5(追加効果)>> 大容量スタッカにも対応可能。



<スタッカ> スタッカをフラットベッド側に付ければ 大容量スタッカ実現。

3【特許請求の範囲】

フラットベッド読取部と、ADF(Auto_Document Feeder)を有するインージスキャ疗装置で、以下の項目を請求の範囲とする。

- 1. イメージスキャナ装置の原稿が一上で ADF1ニッムの向き、位置を自由自在に可変させる構造案。
- 2. ADFモデル、フラットヘット・モデルといった様々なパリエーションモデルを製造側が簡単に設定できる構造。
- 3. ADF に実装されているスタッカをフラットペット 側に付け替えることで、大容量スタッカにも対応可能な構造。 (本発明の図 その5)


1. 目 的

- ①. フラットベッド、ADFの同時読取りを可能にする。
- ②. 装置の占有面積を小さくする。
- ③. 使用する設置環境に合わせ、装置の操作性を変化させる。 上記3点の達成を目的とする。

2. 構成

【当社の従来技術】

2 つの読取りユニットを配備し、ADF使用時の両面読取り及びフラットベッド使用時も兼用構造。 ADFは、装置左側に配備されているため、シュータへの原稿セットは、右利きの人は操作しやすいが、 左利きの人には難しさがあった。



【本発明】

装置に、ADF部の読取りユニット2個 フラットベッド部の読取りユニット1個 計3個の読取り ユニット及び2つのインターフェースを実装し、ADF, FBの同時読取りが行える構造とし、 ADFユニットが装置原稿カバー上の任意の位置に配備でき、かつADFの向きを回転可能とする構造。





EXHIBIT 2

PATENT, UTILITY MODEL APPLICATION REQUEST PAPER

Reception No

03/00040



1. OBJECTS

The present invention relates to an image scanner having a Flatbed-type scanning part and an ADF (Auto Document Feeder).


- ① Operability of the apparatus can be changed in accordance with the installation environment for using the apparatus.
- ② An area occupied by the apparatus can be reduced.
- ③ A wide variety of models, such as the ADF-model, the flatbed-model, etc., can be developed easily by a manufacturing department. The objects of the present inventions are to achieve the above three points.

2. CONFIGURATION

[Prior Art in Our Company]

Two scanning units are provided for the apparatus, and the two scanning units are used in both a both-side scanning in the operation of the ADF and a scanning in the operation of the Flatbed scanning part.

Since the ADF is provided at the left side of the apparatus, it is easy for a right-handed user to set documents on a shooter of the ADF, but it is not easy for a left-handed user to set documents on the shooter. Further, the area of a stacker becomes part of the area occupied by




PATENT, UTILITY MODEL APPLICATION REQUEST PAPER


Reception No. 03 P00040

[Present Invention]

Mechanism: Three scanning units (two scanning units in an ADF part and one scanning unit in a Flatbed scanning part) are mounted, so documents can be read only by using the ADF, the ADF can be mounted at an arbitrary potion on the surface of a document cover of the apparatus, and the direction of the ADF can be rotatable.




<< Figure 1 of the present invention (Regarding the object ①)>>



Reception No. 03700040

<< Figure 2 of the present invention (Regarding the object ②)>>




<< Figure 3 of the present invention (Regarding the object ③)>>

In accordance with the configuration of the present invention, three kinds of scanners including an ADF model, a Flatbed model and an ADF&Flatbed model can be prepared easily without any new research and development by the manufacturing department because the ADF part and the Flatbed part can read documents independently (and three scanning units and the ADF can be detachable from the apparatus freely.).

The following figures indicate the ADF model and the Flatbed model. Further,

the figures suggest that two models can be prepared easily in accordance with the mounted position of a PCB unit (on the ADF model or on the Flatbed model).

It is natural that the ADF&Flatbed model is prepared by mounting the ADF model on the Flatbed model.




Reception No. 03 P00040

<< Figure 4 of the present invention (Technology for achieving the object)>>

The document cover and the ADF are coupled by using a mechanism indicated in the following figures.

Mechanism: Coupling protrusions (nail-like shape) are provided on the bottom surface of the ADF unit and the coupling protrusions are inserted into holes provided on the document cover.

(The direction of the ADF can be changed by using this mechanism.)



Mechanism: A rotatable pivot point and a nail are provided on a slider, and the slider is inserted into a rail mechanism of the document cover so that the slider is moveable to the left and right along the rail mechanism. The direction of the ADF can be changed by using the rotatable pivot point provided on the slider.

The ADF is fixed by a rock mechanism (nail) provided on the slider so that the direction of the ADF is determined.





Figure for coupling mechanism between document cover and ADF

PATENT, UTILITY MODEL APPLICATION REQUEST PAPER

Reception No.

<< Figure 5 of the present invention (Additional effects)>>

The present invention is applicable to a large capacity stacker.



<STACKER>

If the stacker is mounted on the Flatbed-type scanning part, the stacker can be used as a large capacity stacker.

3. CLAIM

An image scanner comprising a Flatbed scanning part and an ADF (Auto Document Feeder), and further including the following mechanisms:

- The direction of the ADF can be changed freely on the surface of a document cover of the image scanner. 1.
- A wide variety of models, such as an ADF-model, a Flatbed-model, etc., can be developed easily by a manufacturing 2. department.
- The stacker can be used as a large capacity stacker if the stacker is replaced from the ADF to the Flatbed-type scanning part (please see figure 5 of the present invention).

1. OBJECTS

The present invention relates to an image scanner having a Flatbed-type scanning part and an ADF (auto-document feeder).


- ① Reading with the Flatbed-type scanning part and reading with the ADF can be performed simultaneously.
- ② An occupied area of the apparatus can be reduced.
- ③ Operability of the apparatus can be changed in accordance with the installation environment for using the apparatus. The objects of the present inventions are to achieve the above three points.

2. CONFIGURATION

[Prior Art in Our Company]

Two scanning units are provided for the apparatus, and the two scanning units are used in both a both-side scanning in the operation of the ADF and a scanning in the operation of the Flatbed scanning part.

Since the ADF is provided at the left side of the apparatus, it is easy for a right-handed user to set documents on a shooter, but it is not easy for a left-handed user to set documents on the shooter.



Mechanism: Three scanning units (two scanning units in an ADF part and one scanning unit in a Flatbed scanning part) and two interfaces are mounted, so reading with the Flatbed-type scanning part and reading with the ADF can be performed simultaneously, the ADF can be mounted at an arbitrary potion on the surface of a document cover of the apparatus, and the direction of the ADF can be rotatable.

